

	P5QLD PRO 2009/9/2
Note: The specifications a	re subject to change without notice.
СРИ	LGA775 socket for Intel® Core™2 Extreme/Core™2 Quad/ Core™2 Duo/Pentium® dual-core/Celeron® dual-core /Celeron® Processors
	Compatible with Intel® 05B/05A/06 processors
	Support Intel® 45nm Multi-Core CPU
Chipset	Intel® P43 / ICH10 with Intel® Fast Memory Access Technology
System Bus	1600(O.C) / 1333 / 1066 / 800 MHz
Memory	4 x DIMM, max. 16GB, DDR2 1066/800 / 667 MHz, non-ECC, un-buffered memory
	Dual channel memory architecture
Expansion Slots	1 x PCle x16
	2 x PCle x1
	3 x PCI
Storage	Southbridge
	- 6 x SATA 3.0 Gb/s ports
	JMB 368
	- 1 x UltraDMA 133/100/66 for up to 2 PATA devices
LAN	PCIe Gb LAN controller featuring Al NET 2
	Realtek ALC 1200, 8-channel High-Definition Audio CODEC
A	- Support Jack Detection and Multi-streaming
Audio	- Coaxial S/PDIF out ports at back I/O
	- ASUS Noise Filter
USB	12 x USB 2.0 ports (6 ports at mid-board, 6ports at back panel)
ASUS Unique Features	ASUS Power Saving Solution:
	- ASUS EPU- 4 Engine
	ASUS AI Life Features:
	- ASUS Express Gate
	ASUS Quiet Thermal Solution:
	- ASUS Fan Xpert
	ASUS Crystal Sound:
	- ASUS Noise Filter
	ASUS EZ DIY:
	- ASUS Q-Connector
	- ASUS O.C. Profile
	- ASUS Q-Connector
	- ASUS CrashFree BIOS 3
	- ASUS EZ Flash 2
Other Features	ASUS MyLogo 2
	Intelligent overclocking tools:
	- ASUS AI Booster utility
	Precision Tweaker:
	- vCore: Adjustable CPU voltage at 6.25mV increment
	- vDIMM: 5-step DRAM voltage control



	- FSB tuning from 200MHz up to 800MHz at 1MHz increment
	- Memory tuning from 667MHz up to 1333MHz for DDR2
	- PCI Express frequency tuning from 100MHz up to180MHz at 1MHz increment
	Overclocking Protection:
	- ASUS C.P.R.(CPU Parameter Recall)
Back Panel I/O Ports	1 x PS/2 Keyboard
	1 x PS/2 Mouse
	1 x S/PDIF Out (Coaxial)
	1 x RJ45 port
	6 x USB 2.0/1.1
	8-channel Audio I/O
	3 x USB connectors support additional 6 USB ports
	1 x Floppy disk drive connector
	1 x IDE connector
	1 x COM connector
	6 x SATA connectors
	1 x CPU Fan connector
	1 x Chassis Fan connector
Internal I/O Connectors	1 x Power Fan connector
	Front panel audio connector
	1 x S/PDIF Out Header
	Chassis Intrusion connector
	CD audio in
	24-pin ATX Power connector
	1 x 4-pin ATX 12V Power connector
	System Panel(Q-Connector)
BIOS	8 Mb Flash ROM, AMI BIOS, PnP, DMI2.0, WfM2.0, SM BIOS 2.3, ACPI 2.0a, ASUS EZ Flash 2, ASUS CrashFree BIOS 3
Manageability	WfM 2.0, DMI 2.0, WOL by PME, WOR by PME, PXE
Accessories	UltraDMA 133/100/66 cable
	2 x Serial ATA cables
	I/O Shield
	User's manual
	2 in 1 Q-connector
Support DVD	Drivers
	ASUS PC Probe II
	ASUS Update
	ASUS AI Suite
	Anti-virus software (OEM version)
Form factor	ATX Form Factor, 12"x 7.6" (30.5cm x 19.3cm)
i omi idotoi	7.17.7. O.III.1. 40.01, 12 x 7.0 (00.00111 x 10.00111)